



CETO

HORIZONTAL CHANDELIER - SINGLE

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Horizontal Chandelier can be easily customised and configured to your project needs.

AVAILABLE FINISHES




TECHNICAL


MATERIAL	ANODISED ALUMINIUM, GLASS						
LOW VOLTAGE LED (220-240V REGIONS)	<p><b>SELV 60V (WITH EXTERNAL DRIVER)</b></p> <p>2-4W LED MODULE, WATTAGE WILL VARY SLIGHTLY DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE. 3000K WARM WHITE.</p> <p><b>DIMMING OPTIONS:</b></p> <ul style="list-style-type: none"><li>· PHASE - DIMMING RANGE 5 - 100%.</li><li>· DALI - DIMMING RANGE 1 - 100%.</li><li>· 1-10V - DIMMING RANGE 5 - 100%.</li><li>· 0-10V - NOT COMPATIBLE.</li></ul> <p>IF THE CEILING CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.</p>						
120V LED (100-120V REGIONS)	<p><b>4W AC LED MODULE</b></p> <p>380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT REQUIRED, DIRECT MAINS VOLTAGE.</p> <p><b>DIMMING OPTIONS:</b></p> <ul style="list-style-type: none"><li>· PHASE - DIMMING RANGE 5 - 100%.</li><li>· DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH.</li><li>· 1-10V - NOT COMPATIBLE.</li><li>· 0-10V - NOT COMPATIBLE.</li></ul> <p>ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.</p> <p>FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.</p> <p>PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION.</p>						
LED LIFESPAN	50,000 HRS						
CERTIFICATION	<table><tr><td>AU/NZ</td><td>AS/NZS 60598.1, 60598.2.1</td></tr><tr><td>EU</td><td>EN 60598.1, 60598.2.1</td></tr><tr><td>US/CAN</td><td>ETL/UL 1598, CSA C22.2#250.0</td></tr></table>	AU/NZ	AS/NZS 60598.1, 60598.2.1	EU	EN 60598.1, 60598.2.1	US/CAN	ETL/UL 1598, CSA C22.2#250.0
AU/NZ	AS/NZS 60598.1, 60598.2.1						
EU	EN 60598.1, 60598.2.1						
US/CAN	ETL/UL 1598, CSA C22.2#250.0						

IP RATING	IP20 - FOR INDOOR USE ONLY	
CANOPY	Ø120 X 30MM CEILING CANOPY. CIRCULAR FINISH AND ANODISED TO MATCH THE SPECIFIED FINISH OF CETO. MOUNTING HOLES TO SUIT STANDARD 4" JUNCTION BOXES FOR THE US/CAN REGION.  AN OPTIONAL Ø170 X 40MM CEILING CANOPY AVAILABLE FOR 220-240V REGION ORDERS WHERE DRIVERS CANNOT BE HOUSED WITHIN CEILING CAVITY.	
PRODUCT CODES SKU	EG. CH12S.G-BLK.A-BLK = CETO HORIZONTAL CHANDELIER IN BLACK GLASS WITH A BLACK ANODISED BODY	
CH12S-G-XXX.A-XXX	HORIZONTAL CHANDELIER WITH 1 X CEILING MOUNTING POINT AND 2 X MODULES, STANDARD SPACING BETWEEN LIGHTS	
CH12L-G-XXX.A-XXX	HORIZONTAL CHANDELIER WITH 1 X CEILING MOUNTING POINT AND 2 X MODULES, LONG SPACING BETWEEN LIGHTS	
CH14S-G-XXX.A-XXX	HORIZONTAL CHANDELIER WITH 1 X CEILING MOUNTING POINT AND 4 X MODULES, STANDARD SPACING BETWEEN LIGHTS	
CH14L-G-XXX.A-XXX	HORIZONTAL CHANDELIER WITH 1 X CEILING MOUNTING POINT AND 4 X MODULES, LONG SPACING BETWEEN LIGHTS	
CHC-G-XXX.A-XXX	HORIZONTAL CHANDELIER WITH A CUSTOM CONFIGURATION	
FINISHES FOR ALL VARIATIONS:	GLASS: FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BODY: BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)	
DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*	
WEIGHT	CH12S/L - 5.5KG / 12.2LB CH14S/L - 6.5KG / 14.3LB	
PACKAGING	L 50CM W 50CM H 25CM / L 20" W 20" H 9.8"	
PACKAGING WEIGHT	CH12S/L - 6KG / 13.2LB CH14S/L - 7KG / 15.5LB	


DIMENSIONS




CH12S  
L 866 W 174 H 200^  
L 35" W 6.9" H 7.9"^




CH14S  
L 866 W 174 H 200^  
L 35" W 6.9" H 7.9"^



CH12L  
L 866 W 174 H 200^  
L 35" W 6.9" H 7.9"^



CH14L  
L 866 W 174 H 200^  
L 35" W 6.9" H 7.9"^



CHC\*  
L 866 W XXX H XXX^  
L 35" W XXX" H XXX"^

\*CUSTOM CONFIGURATIONS AVAILABLE UPON REQUEST  
^ HANG HEIGHT NEEDS TO BE CONFIRMED PRIOR TO PRODUCTION  
H - INDICATED MINIMUM HANG HEIGHT (CEILING TO BOTTOM OF GLASS)