



CETO
PENDANT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. This sculptural luminaire is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. The Ceto Pendant Light softly illuminates a space, providing a tranquil calming light.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS	IP RATING	IP20 - FOR INDOOR USE ONLY
LOW VOLTAGE LED (220-240V REGIONS)	<p>SELV 60V (WITH EXTERNAL DRIVER) 2-4W LED MODULE, WATTAGE WILL VARY SLIGHTLY DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN RANGE PER LIGHT SOURCE. 3000K WARM WHITE.</p> <p>DIMMING OPTIONS:</p> <ul style="list-style-type: none">· PHASE - DIMMING RANGE 5 - 100%· DALI - DIMMING RANGE 1 - 100%· 1-10V - DIMMING RANGE 5 - 100%· 0-10V - NOT COMPATIBLE <p>IF THE CEILING CAVITY CANNOT HOUSE THE DRIVER PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.</p>	CORD	2M / 6.6' SUPPLIED DOUBLE INSULATED CABLE COVERED BY A DURABLE BLACK OR WHITE CLOTH COVER. LONGER LENGTHS AVAILABLE UPON REQUEST.
		CANOPY	<p>Ø120 X 30MM CEILING CANOPY. CIRCULAR LINISH AND ANODISED TO MATCH THE SPECIFIED FINISH OF CETO. MOUNTING HOLES TO SUIT STANDARD 4" JUNCTION BOXES FOR THE US/CAN REGION.</p> <p>NOTE: AN OPTIONAL Ø170 X 40MM CEILING CANOPY AVAILABLE FOR 220-240V REGION ORDERS WHERE DRIVERS CANNOT BE HOUSED WITHIN CEILING CAVITY.</p>
120V LED (100-120V REGIONS)	<p>4W AC LED MODULE 380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT REQUIRED, DIRECT MAINS VOLTAGE.</p> <p>DIMMING OPTIONS:</p> <ul style="list-style-type: none">· PHASE - DIMMING RANGE 5 - 100%.· DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY VIA DALI SWITCH (NOT SUPPLIED).· 1-10V - NOT COMPATIBLE.· 0-10V - NOT COMPATIBLE. <p>ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS.</p> <p>FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A ROTARY OR PUSH BUTTON DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.</p> <p>PLEASE CONTACT OUR STUDIO FOR FURTHER INFORMATION REGARDING MOST SUITABLE LAMPING TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION.</p>	PRODUCT CODES SKU EG. CP1-G-BLK.A-BLK = CETO PENDANT - SINGLE IN BLACK GLASS WITH A BLACK ANODISED BODY	<p>CP1-G-XXX.A-XXX CETO PENDANT- SINGLE CP3-G-XXX.A-XXX CETO PENDANT- TRIPLE CP7-G-XXX.A-XXX CETO PENDANT- SEVEN</p> <p>FINISHES:</p> <p>GLASS: FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BODY: BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)</p>
		DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*
		WEIGHT	CP1 - 1.5KG / 3LB CP3 - 4.5KG / 10LB CP7 - 7.5KG / 23LB
		PACKAGING	CP1 - L 25CM W 25CM H 25CM / L 9.8" W 9.8" H 9.8" CP3 - L 50CM W 50CM H 25CM / L 20" W 20" H 9.8" CP7 - 2 X L 50CM W 50CM H 25CM / L 20" W 20" H 9.8"
		PACKAGING WEIGHT	CP1 - 2KG / 4.4LB CP3 - 5KG / 11LB CP7 - 2 X 4KG / 8.8LB
LED LIFESPAN	50,000 HRS		
CERTIFICATION	AU/NZ AS/NZS 60598.1, 60598.2.1 EU EN 60598.1, 60598.2.1 US/CAN ETL/UL 1598, CSA C22.2#250.0		

DIMENSIONS



CP1
Ø 200 H 105
Ø 7.9" H 4.1"



CP3
Ø410 H 120
Ø16.1" H 4.7"



CP7
Ø 590 H 130
Ø23.2" H 5.1"
*MINIMUM DROP HEIGHT
REQUIREMENTS - SEE BELOW.

* CP7 MINIMUM DROP HEIGHT WITH SUPPLIED CABLE SUSPENSION TUBE IS 1050MM / 3'5". ALTERNATIVELY REMOVE THE CABLE SUSPENSION TUBE AND HANG THE FIXTURE AT 700MM / 2'4" TO ENSURE CORRECT BALANCE BETWEEN PENDANTS.