

CETO

LINEAR WALL LIGHT

Ceto captures the variation and rippling of the surface of the ocean. Each piece reflects a unique pattern, emitting a delicate luminosity, highlighting the presence of the sea. The Ceto Linear Wall light is available in a selection of mouth-blown glass finishes combined with a highly refined machined aluminium body available in a black and champagne anodised finish. Each glass piece is designed to rotate around the central stem, reflecting the shadows of the glass against the wall, replicating the natural flow and movement of water.

## AVAILABLE FINISHES




## TECHNICAL

MATERIAL	ANODISED ALUMINIUM, GLASS	MOUNTING	WALL MC
LOW VOLTAGE LED	SELV 60V (WITH EXTERNAL DRIVER)		BOXES A
(220-240V REGIONS)	2-4W LED MODULE, WATTAGE WILL VARY SLIGHTLY		SUPPLIED
	DEPENDING ON CETO CONFIGURATION. 300-380 LUMEN		DESIGNE
	RANGE PER LIGHT SOURCE. 3000K WARM WHITE.		
		LED LIFESPAN	50,000 H
	DIMMING OPTIONS:		
	PHASE - DIMMING BANGE 5 - 100%.	CERTIFICATION	AU/NZ
	· DALL - DIMMING BANGE 1 - 100%.		FU
	· 1-10V - DIMMING BANGE 5 - 100%.		US/CAN
	· 0-10V - NOT COMPATIBLE.		00/0/11
	IF THE WALL CAVITY CANNOT HOUSE THE DRIVER	IP BATING	IP20 - FO
	PLEASE CONTACT THE STUDIO FOR FURTHER OPTIONS.		
		PRODUCT CODES SKU	
120V LED	4W AC LED MODULE	EG. CWL3.G-BLK.A-BLK = CETO L	
(100-120V REGIONS)	380 LUMEN PER LIGHT SOURCE. 3000K WARM WHITE, DIMMABLE. DRIVER NOT REQUIRED, DIRECT MAINS	BLACK ANODISED BOD	Y
	VOLTAGE.	CWL3.G-XXX.A-XXX	CETO LIN
	VOLIAGE.		
	DIMMING OPTIONS:	FINISHES FOR ALL	
	· PHASE - DIMMING RANGE 5 - 100%.	VARIATIONS:	GLASS: F
	· DALI - NON-DIMMABLE, ON/OFF FUNCTIONALITY ONLY		В
			С
			V
	- 1-10V - NOT COMPATIBLE.		BODY: B
	· 0-10V - NOT COMPATIBLE.		С
	FOR OPTIMAL DIMMING PERFORMANCE WE	DIMENSIONS	VARIOUS
	RECOMMEND SOURCING A ROTARY OR PUSH BUTTON	DIVIENSIONS	VARIOUS
		WEIGHT	CWL3 - 7
	DIMMER WITH ADJUSTMENT DIAL CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	11 El Gilli	01120
		PACKAGING	CWL3 - L
	PLEASE CONTACT OUR STUDIO FOR FURTHER		0.14/1 0 7
	INFORMATION REGARDING MOST SUITABLE LAMPING	PACKAGING WEIGHT	CWL3 - 71
	TECHNOLOGY FOR YOUR SPECIFIC PROJECT/REGION		

MOUNTING	WALL MOUNT BODIES Ø50MM / 2". TO ENSURE CORRECT COVERAGE OVER 4" JUNCTION BOXES ADDITIONAL Ø120MM / 4.7" COVER PLATES ARE SUPPLIED FOR 100-120V REGIONS. MOUNTING HOLES DESIGNED TO SUIT STANDARD 4" JUNCTION BOXES.			
LED LIFESPAN	50,000 HRS			
CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 ETL/UL CERTIFICATION PENDING		
IP RATING	IP20 - FOR INDOOR USE ONLY			
PRODUCT CODES SKU EG. CWL3.G-BLK.A-BLK = CETO LINEAR WALL LIGHT IN BLACK GLASS WITH A BLACK ANODISED BODY				
CWL3.G-XXX.A-XXX	CETO LINEAR WALL LIGHT WITH OFFSET MOUNT			
FINISHES FOR ALL VARIATIONS:	BL CL WF BODY: BL	GLASS: FROSTED BLACK (G-FBK) BLACK (G-BLK) CLEAR (G-CLR) WHITE (G-WHT) BODY: BLACK ANODISED (A-BLK) CHAMPAGNE ANODISED (A-CHM)		
DIMENSIONS	VARIOUS - SEE DIMENSIONS ON FOLLOWING PAGE*			
WEIGHT	CWL3 - 7 KG / 15.4LB			
PACKAGING	CWL3 - L 75CM W 50CM H 25CM / L 30" W 20" H 9.8"			
PACKAGING WEIGHT	CWL3 - 7K0	G / 15.4LB		

## DIMENSIONS



CWL3 W 200 H 1010 D 140 W 7.9" H 40" D 5.5"