



VOLANT

WALL LIGHT

Volant features solid brass bars, paired with textured, tubular formed-glass elements, creating a statement luminaire. This delicate light creates an equilibrium between the different materials and offers a beautifully soft level of luminosity.

Volant’s architectural nature allow the fixture to span across a plethora of interior spaces. The solid brass bars are individually machined with the luminaire defined by a white glass diffuser which is pinned in-place to the solid brass bar. Textured tubular glass elements are balanced on the same pins creating a uniquely formed illumination.

AVAILABLE FINISHES



TECHNICAL

MATERIAL	TREATED BRASS, GLASS	CERTIFICATION	AU/NZ EU US/CAN	AS/NZS 60598.1, 60598.2.1 EN 60598.1, 60598.2.1 ETL/UL CERTIFICATION PENDING
FINISH	ALL BRASS FRAMES ARE BRUSHED AND TREATED TO ACHIEVE THE AVAILABLE FINISH OPTIONS, THEN SEALED TO PREVENT ACCELERATED AGING.	WALL MOUNT DIMENSIONS	VW1 - H 330 X W 22 / H 13" X W 0.9" VW2 - H 330 X W 15.5 / H 13" X W 0.6"	
LAMPING	SELV 60V (EXTERNAL DRIVER SUPPLIED) VW1 - 5.3W, 766 LM, 2700K VW2 - 7.8W, 1186 LM, 2700K			TO ENSURE CORRECT COVERAGE OVER 4" JUNCTION BOXES AN ADDITIONAL MOUNTING PLATE (Ø110MM / 4.3") & COVER PLATE (250MMH X 120MMW / 9.9"H X 4.7"W) IS SUPPLIED FOR US/CAN REGIONS. MOUNTING HOLES DESIGNED TO SUIT STANDARD 4" OCTAGONAL JUNCTION BOXES. MOUNT & COVER PLATES ARE NOT SUPPLIED FOR OTHER REGIONS.
DIMMING OPTIONS	220-240V REGION PHASE - DIMMING RANGE 5 - 100% DALI - DIMMING RANGE 1 - 100% 110-120V REGION PHASE - DIMMING RANGE 3 - 100% DALI - DIMMING RANGE 0.1 - 100% ALL US AND CANADIAN ORDERS COME SUPPLIED WITH 120V COMPONENTRY CERTIFIED FOR USE IN THESE REGIONS. FOR OPTIMAL DIMMING PERFORMANCE WE RECOMMEND SOURCING A DIMMER CAPABLE OF SETTING THE DIMMING RANGE OF THE FIXTURE.	SKU CODES	EG. VW2.G-FLU.BR-BRZ VOLANT DOUBLE WALL LIGHT IN FLUTED CLEAR GLASS WITH A BRONZED BRASS FRAME VW1.G-XXX.BR-XXX VW2.G-XXX.BR-XXX	VOLANT SINGLE WALL LIGHT VOLANT DOUBLE WALL LIGHT
DRIVER SIZE 220 -240V	PHASE / TRIAC ALL VW - L101 X W51 X H29 / L4" X W2" X H1.1" DALI ALL VW - L120 X W51 X H29 / L4.7" X W2" X H1.1"	FINISHES GLASS	FROSTED BLACK (G-FBL) FLUTED (G-FLU) FROSTED FLUTED (G-FFL)	
		FRAME	BRUSHED BRASS (BR-NAT) BLACKENED BRASS (BR-BLK) BRONZED BRASS (BR-BRZ)	
110-120V	PHASE / TRIAC ALL VW - L75 X W35 X H26.5 / L3" X W1.4" X H1" DALI ALL VW - L88 X W43 X H26.5 / L3.5" X W1.7" X H1"	PRODUCT WEIGHT	VW1 2KG / 4.4LB VW2 5KG / 11LB	
		PACKAGING WEIGHT	VW1 1 X 3KG / 6.6LB VW2 1 X 6KG / 13.2LB	
LED LIFESPAN	50,000 HRS	PACKAGING SIZE	VW1 L 550 W 260 H 100 / L 21.6" W 10.3" H 4" VW2 L 550 W 340 H 100 / L 21.6" W 10.3" H 4"	
IP RATING	IP20 - FOR INDOOR USE ONLY			

DIMENSIONS



VW1
W 70 H 500 D 80
W 2.8" H 19.7" D 3.2"



VW2
W 160 H 500 D 80
W 6.3" H 19.7" D 3.2"

*DOTTED LINE REPRESENTS
OPTIONAL JUNCTION BOX COVER PLATE